



シェル挿入方向キー
POLARIZATIONS KEY FOR SHELL

注)
NOTES

- 適用プラグシェルアッセンブリ : 58782-0010
APPLICABLE PLUG SHELL ASS'Y : 58782-0010
- 適用エンドベルキャップセット : 58550-****
APPLICABLE END BELL CAP SET : 58550-****

⑤	ノブ KNOB	ポリブチレンテレフタレート, UL 94V-0, 黒 POLYBUTYLENE TELEPHTHALATE, UL94V-0, BLACK	1	
④	レバー LEVER	鋼 STEEL	1	
③	ロックピン LOCKING PIN	ステンレス STAINLESS STEEL	2	58462-0010
②	スプリング SPRING	ステンレス STAINLESS STEEL	2	
①	プラグカバー PLUG COVER	アルミニウム合金 ALUMINIUM ALLOY	1	
部番 NO.	部品名 PARTS NAME	材質 MATERIAL	個数 QUAN.	製品番号 ENG. NO.

REVISED EC NO: J2009-1220 DRWN: YOSHIDAM 2008/12/15 CHKD: THARUYAMA 2008/12/15 APPR: NUKITA 2008/12/16	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY	SCALE 1:1	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION
	10 UNDER	±0.2	DRAWN BY J. MIYAZAWA	TITLE ROBOT CONN S/T PLUG COVER ASSY FOR LARGE SHELL SHEET 1 OF 2		
	10 OVER 30 UNDER	±0.25	CHECKED BY Y. ITO	MOLEX INCORPORATED		
	30 OVER	±0.3	APPROVED BY H. IKESUGI	DOCUMENT NO. SD-58462-001	SHEET NO. 1 OF 1	
REV	DESCRIPTION	ANGULAR ±3 ° DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	SIZE A3	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		